410 Rec'd PCT/PTO 2 3 DEC 1999

	Form PTO-1390	U.S. DEPARTMENT OF COMP PATENT AND TRADEMARK OF		ATTORNEY'S DOCKET NUMBER				
	TRANSMITTAL LETTER TO DESIGNATED/ELECTED	OFFICE (DO/EO/US)		TUR-087 U.S. APPLICATION NO				
	CONCERNING A FILING OF THE CONCERNING O	UNDER 35 U.S.C. 3/1 INTERNATIONAL FILING DATE	010	09/446630 PRIORITY DATE CLAIMED:				
	PCT/F198/00572	July 6, 1998		July 8, 1997				
į	TITLE OF INVENTION NOVEL PLASTIC BASED COMPOSITE AND ITS US		P 2 3 1889 SS	DATE: December 23, 1999				
	APPLICANT(S) FOR DO/EO/US Allan AHO, Jukka SEPPALA, Antti YLI-URPO	, Jouni HEIKKILA, Ilkka KANG	ASNI MA ADEMARK OFFICE					
į	Applicant herewith submits to the United information:			lowing items and other				
	l 1. [XX] This is a FIRST submission of i	tems concerning a filing unde	er 35 U.S.C. 371.					
	2. [] This a SECOND or SUBSEQUENT sub	mission of items concerning a	a filing under 35 U.S.C.	371.				
	3. [XX] This express request to begin necessation examination until the expiration			any time rather than delay)) and PCT Articles 22 and 39(1).				
	[XX] A proper Demand for Internation priority date.	al Preliminary Examination wa	as made by the 19th month	n from the earliest claimed				
STATE AND ADDRESS	[XX] A copy of the International Application as filed (35 U.S.C. 371(c)(2)) a. [] is transmitted herewith (required only if not transmitted by the International Bureau). b. [XX] has been transmitted by the International Bureau. c. [] is not required, as the application was filed in the United States Receiving Office (RO/US).							
:	[] A translation of the International Application into English (35 U.S.C. 371(c)(2)).							
	[] A translation of the International Application into English (35 U.S.C. 371(c)(2)). [XX] Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C 371(c)(3)) a. [] are transmitted herewith (required only if not transmitted by the International Bureau). b. [] have been transmitted by the International Bureau. c. [] have not been made; however, the time limit for making such amendments has NOT expired. d. [XX] have not been made and will not be made.							
	[] A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).							
	[] An oath or declaration of the in	[] An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)).						
	[XX] A translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)).							
		in the second statement of the second statement of the second sec						
	[] An assignment document for reco	rding. A separate cover she	et in compliance with 37	CFR 3.28 and 3.31 is included.				
,	[XX] A FIRST preliminary amendment. [] A SECOND or SUBSEQUENT prelimin	ary amendment.						
	14. [] A substitute specification.							
	15. [] A change of power of attorney a	nd/or address letter.						
	16. [XX] Other items or information:							
	a. WO 99/02201 b. International Search Report (c. International Preliminary Exa		9)					
	1							

514 Rec'd FCT/PTO 2 3 DEC 1999

U.S. Applicat	U.S. Application No. PCT/FI98/00572				Attorney's Docket No. TUR-087	
17. [XX] The f	following fees are submitte	d:			CALCULATIONS	PTO USE ONLY
Basic Searc	: National Fee (37 CFR 1.49 h Report has been prepared	2(a)(1)-(5)): by the EPO or JPO.		840.00		
Inter	national preliminary exami	nation fee paid to	USPTO (37 CFR 1.482) \$	670.00		
No in but i	ternational preliminary ex nternational search fee pa	690.00				
Neith inter	er international prelimina national search fee (37 CFI	ry examination fee R 1.445(a)(2)) paid	(37 CFR 1.482) nor to USPTO	970.00		
 Inter	national preliminary examin 11 claims satisfied provis	nation fee paid to	USPTO (37 CFR 1 482)			
		ENTER APPROPR	IATE BASIC FEE AMOUNT	=	\$ 970.00	
Surcharge of months from the	\$130.00 for furnishing the he earliest claimed priorit	oath or declaration by date (37 CFR 1.49	n later than [] 20 [92(e)).] 30	\$	
CLAIMS	NUMBER FILED	NUMBER EXTRA	RATE	*-		
Total claims	17 - 20	0	x \$ 18.00		\$	
Indep.claims	1 - 3	0	x \$ 78.00		\$	
Multiple deper	ndent claim(s) (if applicab	le)	+ \$260.00		\$	
		то	TAL OF ABOVE CALCULATIONS	_	\$970.00	
Reduction by 1 statement must	1/2 for filing by small ent t also be filed. (Note 37	ity, if applicable. CFR 1.9, 1.27, 1.28	. Verified Small Entity 3).		\$	
3 A. C.			SUB TOTAL	=	\$970.00	
Processing feet months from the	e \$130.00 for furnishing the earliest claimed priorit	e English translati y date (37 CFR 1.49	ion later than [] 20 [] 22(f)).] 30	\$	
Section 1			TOTAL NATIONAL FEE	=	\$970.00	
Fee for record accompanied by	ding the enclosed assignmen an appropriate cover shee	t (37 CFR 1.21(h)). t (37 CFR 3.28, 3.3	The assignment must be \$1). \$40.00 per property	+	\$	
\$ E 177			TOTAL FEES ENCLOSES) =	\$970.00	
					Amount to be: refunded	\$
					charged	\$
b.[]Pleas	in the amount of \$970.00 e charge my Deposit Accounopies of this sheet are en	t No. <u>50-0788</u> in		_ to cove	er the above fees	
c. [xx] The C any o	ommissioner is hereby authorepayment to Deposit Accord	orized to charge an unt No. <u>50-0788</u> .	y additional fees which n Two copies of this sheet	nay be re	equired, or credit closed.	
NOTE: Where or (b)	an appropriate time limit) must be filed and grante	under 37 CFR 1.494 d to restore the ap	or 1.495 has not been met plication to pending stat	a peti	ition to review (3	37 CFR 1.137(a)
SEND ALL CORRE	SPONDENCE TO:			Signatu	un L. hydon ire	
100 D	& Brown, LLP aingerfield Road			<u>Dames (</u> Name	C. Lydon/	
Suite Alexa	100 ndria, Virginia 22314			30.082 Registr	ration Number	
	<u>l</u>					9

410 Rec'd PCT/PTO 2 3 DEC 1999

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re the National Stage application of:

Box PCT

Allan AHO et al.

Serial Number: New Application

Group Art Unit:

Filed: December 23, 1999

Examiner:

For: NOVEL PLASTIC BASED COMPOSITE AND ITS USE

PRELIMINARY AMENDMENT

Assistant Commissioner for Patents Washington, D.C. 20231

December 23, 1999

Sir:

Please amend this application, prior to calculation of the filing fee, as follows:

IN THE CLAIMS:

Please amend claims 3, 4, 10 and 12-17 as follows:

Claim 3, line 1, delete "or 2".

Claim 4, line 1, delete "2 or 3,".

Claim 10, line 1, change "any of the above claims" to -- claim 1 --.

Claim 12, line 1, change "any of the above claims" to -- claim 1 --.

Claim 13, line 1, change "any of the above claims" to -- claim 1 --.

Claim 14, line 1, change "any of Claims 1 - 12" to -- claim 1

Claim 15, line 2, change "any of Claims 1 - 14" to -- claim 1

--.

New U.S. Patent Application PRELIMINARY AMENDMENT

PATENT

Claim 16, line 3, change "any of Claims" to -- claim 1 --; line 4, delete "1 - 14".

Claim 17, line 1, change "any of Claims 1 -" to -- claim 1 --; line 2, delete "14".

IN THE ABSTRACT:

Please add the attached Abstract of the Disclosure after the claims.

REMARKS

This Preliminary Amendment eliminates multiple dependencies from claims 3, 4, 10, and 12-17 and presents a new abstract based on the PCT abstract. Claims 1-17 are pending.

It is not believed that any fee is required for entry and consideration of this Preliminary Amendment. Nevertheless, the Commissioner is authorized to charge our Deposit Account No. 50-0788 in the amount of any fee deemed necessary to effect such entry and consideration.

New U.S. Patent Application PRELIMINARY AMENDMENT

PATENT

Prompt and favorable examination of this application are earnestly requested.

Respectfully submitted,

LYDON & BROWN, LLP

James C. Lydon Reg. No. 30,082

Atty. Case No. <u>TUR-087</u>

100 Daingerfield Road Suite 100

Alexandria, VA 22314

Telephone: (703) 838-0445 Facsimile: (703) 838-0447

Enclosure:

Abstract of the Disclosure

ABSTRACT OF THE DISCLOSURE:

A composite intended for medical, in particular surgical or therapeutic use, which includes a thermoplastic component and a bioactive component. The thermoplastic component is plasticizable within the temperature range -10°C to +100°C, and is substantially made up of hydroxy acids or structural units derived from hydroxy acid derivatives, the molar mass of which is within the range 10,000 - 1,000,000 g/mol, and which degrades in the body typically within a period ranging from a few days to several years, and which in its solid state is a mechanically strong plastic or rubbery material. The bioactive component is a bioactive glass, a bioactive xerogel, a bioactive ceramic material, coral or a coralbased product, or a bioactive glass ceramic material. The invention also relates to the use of the novel composite and to products made therefrom.

SMALL ENTITY DECLARATION

•	A DDF 16	~ 4 N/T (A)	R PATENTEE Bioxid	LL ENITTY DEC		PO TO THE PROPERTY OF THE PARTY			
				PATENT NO					
ieck o	ne			cember 23, 1999	DOCKET No	0. <u>TUR-087</u>			
blocks	5								
or 2)			☐ SUBMITTED HEREWITE	н ed composite and	i + g 11 g A				
	FOR _	1,0,0	Plabolo babe	(Insert Title)	105 050				
	identi	ned app	declare that I(we) am(ar lication or patent for purk Office.	re) entitled to the benefit o poses of paying reduced fee	f small entity status with a sunder 35 USC 41(a) & (respect to the above- (b) to the U.S. Patent			
		A.	INDEPENDENT INVENTOR I(we) qualify as (an) ind	R dependent inventor(s) as def	ined in 37 CFR 1.9(c).				
		В.	INDIVIDUAL NON-INVENT	TOR dependent inventor as define	d in 37 CFR 1.9(c) if I had	d made the invention.			
	X	X C. SMALL BUSINESS CONCERN							
Bank Thous stakes stall B B B B B B B Bank Bank	I am \square THE OWNER \boxtimes AN OFFICIAL of the small business concern identified below and am empowered to act on behalf of the concern. The concern qualifies under 37 CFR 1.9(d) and 13 CFR 121.1301-1305. Rights under contract or law have been conveyed to and remain with the concern and are exclusive unless a checkmark is placed here \square . All other rights belong to small entities as defined in 37 CFR 1.9.								
		D.	NON-PROFIT ORGANIZAT	ION					
	I am an official am empowered to act on behalf of the non-profit organization identified below. The organization qualifies under 37 CFR 1.9(e), sub section: \Box (1) \Box (2) \Box (3) \Box (4). Rights under contract or law have been conveyed to and remain with the organization and are exclusive unless a checkmark is placed here \Box . All other rights belong to small entities as defined in 37 CFR 1.9.								
user badi bane iban ikan hadi	of enti mainte	tlement nance f leclare	to small entity status price due after the date on v	his application or patent, not for to paying, or at the time which status as a small entituded under the laws of the United	e of paying, the earliest of y is no longer appropriate.	the issue fee or any (37 CFR 1.28(b)).			
			DENT INVENTOR(S)	B. INDIVID	JAL NON-INVENTORS				
	Name			Signature		Date			
	Name			Signature		Date			
	Name			Signature		Date			
	С. в	USINES	S CONCERN	D. NON-PROFIT ORG	ANIZATION				
		xid Concern	Oy or Organization		enpunojankatu 2 s Finland	B 5, FIN-20300 T			
	Name of	Person	Signing Jolle		rry Jalonen				
	_	/,	- V - \ \ /		21.1.200				

SMALL ENTITY DECLARATION

A	APPLICAN	T O	R PATENTEE JVS-P	olymers Oy		-	图	000 S)
SI	ERIAL N	o	09/446,630 □ PA	TENT NO		DOCKET NO.	rur 087	artick)
ck one	•	1.	☑ FILED OR ISSUED De	cember 23,1	999		MARK	
ocks		2.	☐ SUBMITTED HEREWITH					
2) F	OR		Novel plastic 1					_
				(Insert Ti	tle)			
id	dentified	app	declare that I(we) am(are) dication or patent for purpork Office.	entitled to the beroses of paying reduce	nefit of small entity and fees under 35 US	status with resp SC 41(a) & (b) t	ect to the above to the U.S. Pate	ve- ent
		A.	INDEPENDENT INVENTOR I(we) qualify as (an) indep	pendent inventor(s)	as defined in 37 CF	R 1.9(c).		
]]	В.	INDIVIDUAL NON-INVENTO I would qualify as an inde		defined in 37 CFR	1.9(c) if I had m	ade the invention	on.
er 1:	I am □ THE OWNER ₺ AN OFFICIAL of the small business concern identified below and am empowered to act on behalf of the concern. The concern qualifies under 37 CFR 1.9(d) and 13 CFR 121.1301-1305. Rights under contract or law have been conveyed to and remain with the concern and are exclusive unless a checkmark is placed here □. All other rights belong to small entities as defined in 37 CFR 1.9.						01-	
		D.	NON-PROFIT ORGANIZATIO)N				
	I am an official am empowered to act on behalf of the non-profit organization identified below. The organization qualifies under 37 CFR 1.9(e), sub section: \Box (1) \Box (2) \Box (3) \Box (4). Rights under contract or law have been conveyed to and remain with the organization and are exclusive unless a checkmark is placed here \Box . All other rights belong to small entities as defined in 37 CFR 1.9.						or	
of	I(we) acknowledge the duty to file, in this application or patent, notification of any change in status resulting in loss of entitlement to small entity status prior to paying, or at the time of paying, the earliest of the issue fee or any maintenance fee due after the date on which status as a small entity is no longer appropriate. (37 CFR 1.28(b)).						ny	
	(we) dec orrect.	lare	under penalty of perjury un	der the laws of the	United States of Ame	erica that the for	egoing is true a	nd
A	A. IND	EPE	NDENT INVENTOR(S)	B. IN	IDIVIDUAL NON-INVE	ENTORS		
Na	ame			Signature			Date	
Na	ame			Signature			Date	_
Na	ame			Signature			Date	
C	. BUS	INES	S CONCERN	D. NON-PROF	IT ORGANIZATION			
$\frac{J}{N_2}$	JVS-P	oly	ymers Oy n or Organization		Mäkipellont Address / Kinl		FIN-00320	O_Helsin
	Jole	4a	Sepala		Julh Se	exit		_
N	apple of Po	erson	signing nan of the boar	~/	Signature 29 11	1999		
Ti	itle	-	The sound	ч ,	Date	المال المال		

NOVEL PLASTIC BASED COMPOSITE AND ITS USE

The invention relates to a composite which contains a plastic-based bioactive component and is intended for medical, in particular surgical or therapeutic, use.

BACKGROUND OF THE INVENTION AND STATE OF THE ART

5 To elucidate the background of the invention and the state of the art, the publications used, to which reference is made below, are to be viewed as being incorporated into the description of the invention below.

Previously known composites made up of a plastic component 10 and a bioactive component include combinations of hydroxyapatite and methylmethacrylate (literature references (1) - (5).

However, a thermoplastic, plasticizable at a relatively low temperature, has not been used as the plastic component in 15 the known composites mentioned above.

OBJECT OF THE INVENTION

The object of the invention is to provide a novel composite which is intended for medical use, in particular surgical or therapeutic use, and which contains a thermoplastic 20 component and can be machined and molded into a piece-like, coherent, shock-resistant and load-resistant form.

It is a particular object to provide a composite which can be plasticized at a relatively low temperature.

It is also an object of the invention to provide a 25 composite which is moldable for a certain period even after

o o pilalik supikel olmanaro

its temperature has been lowered to a temperature below the setting temperature of the plastic component.

It is a further object of the invention in particular to provide a composite in which the biodegradability, 5 plasticization temperature and setting rate of the plastic component can be controlled separately.

SUMMARY OF THE INVENTION

The characteristics of the invention are given in Claim 1. A composite according to the invention is characterized in 10 that it comprises

- a thermoplastic component, plasticizable within a temperature range of -10 °C...+100 °C, which is substantially made up of hydroxy acids or structural units derived from hydroxy acid derivatives, which has a molar 15 mass within a range of 10,000 - 1,000,000 g/mol, and which degrades in the body typically within a period ranging from a few days to several years, and which in its solid state is a mechanically strong plastic or rubbery material and - a bioactive component, which is a bioactive glass, a bioactive xerogel, a bioactive ceramic material, or a bioactive glass ceramic material.

PREFERRED EMBODIMENTS AND A DETAILED DESCRIPTION OF THE INVENTION

The term "medical" is to be understood in the wide meaning 25 of the word and thus also covers dental and veterinary applications.

Bioactive component

By the bioactive component used in the composite according to the present invention is meant a material which reacts 30 in the physiological conditions of the body. The bioactive component may have one or more of the following properties:

bondable to tissues, bioresorbable, bondable/resorbable, releasing active agents, mineralizing, biocompatible, and antimicrobial. The bioactive component is a bioactive glass, a bioactive ceramic material, a bioactive glass 5 ceramic material, coral or a coral-based product, or a bioactive xerogel. The concept of bioactivity is discussed in, for example, Heikkilä's doctoral dissertation (Ref. 1).

In a composite according to the invention, the bioactive component is present as particles separate one from 10 another. The word "particle" here covers particles of different sizes and shapes, such as fibers, solid or porous pieces, rods, microparticles and glass beads.

The bioactive glasses described in references (1) - (5) can be mentioned as examples of suitable bioactive glasses.

Suitable bioactive ceramic materials include Ca phosphates, such as hydroxyapatite.

An especially suitable bioactive component is xerogel. By xerogel is meant a dried gel, which is described in the literature (9, 11). Silica xerogels are partly hydrolyzed 20 oxides of silicon. Hydrolyzed oxide gels can be produced by the sol-gel process, which has been used for the production of ceramic and glass materials for many years.

The sol-gel process is based on the hydrolyzation of metal alkoxides and a subsequent polymerization of the metal hydroxides. As the polymerization reaction progresses, additional chains, rings and three-dimensional networks are formed, and a gel, made up of water, the alcohol of the alkoxy group and the gel itself, is formed. The sol may also contain other additives, such as acids or bases, which 30 are used for the catalysis of the reaction. If the alcohol and the water are removed thereafter from the gel by washing and evaporation, a xerogel is obtained.

The polymerization of the remaining OH groups continues during the drying. The polymerization continues for a long time even after the gelation. This is called aging. The further the polymerization proceeds, the more stable the 5 gel or xerogel becomes. At room temperature, however, the polymerization will in fact stop after an ageing of a few weeks, and the xerogel will not become completely inert. If the temperature is raised, the polymerization reaction can be accelerated, the gel becomes more stable and shrinkage 10 occurs, and internal stresses appear in the xerogel to an increasing degree.

If the temperature is raised to a sufficiently high level (approx. 1000 °C for monolithic silica gels), the gel or xerogel becomes a pure oxide and no OH groups are left in 15 the material. However, in the case of pure oxides, the dissolution reaction rate is very slow. If the oxides are added together with other ions, such as Na, K, Mg or Ca, the reaction rate can be greatly increased. By these methods, bioactive glasses have been developed, which can form a silica gel layer on their surface through an ion exchange reaction. The dissolution rate of these glasses is controlled by the composition and surface area of the glass. The glasses are melted at a temperature above 1000 °C. Therefore it is not possible to add any organic 25 compounds to the structure of the glass.

Sol-Gel glasses have been used, for example, as implant materials, in particular in bone implants (11). These materials do not dissolve completely. The material is formed at a high temperature, and organic compounds cannot 30 be incorporated into its structure. Klein et al. described that when used as implants, silica gels sintered at a lower temperature caused a strong cell reaction in macrophages and in lymphocytes.

Plastic component

The thermoplastic component used in the present invention, plasticizable within a temperature range of - 10 °C...+100 °C, may be to a varying degree biodegradable or even bioactive. The term "biodegradable" covers all plastics which are not inert. This group thus includes all bioresorbable plastics (degrading under the action of cells) and biodegradable plastics (degrading under the effect of mere moisture). The use of the composite will determine whether it is expedient to select a plastic which is biodegradable at a slower or a more rapid rate.

Biodegradable types of plastic are suitable for most of the uses of the composite according to the invention. A biodegradable plastic component disappears at the desired 15 rate or is biologically nearly stable, and thus promotes the tissue contact and the desired tissue reaction of the bioactive component. The plastic of the composite thus keeps the particles of the bioactive component in place but does not necessarily prevent the bioactive material from 20 coming into contact with tissue fluid. Since the plastic component gradually decomposes, the water of the tissue fluid comes through diffusion into contact with the bioactive component. Likewise, ions and any active additives released from the bioactive material can become diffused through the plastic and affect their surroundings. 25 The surrounding and/or contact surface tissue grows, filling the void formed by the degradation of the plastic. Ultimately the plastic component decomposes completely and releases any possibly remaining bioactive component.

Alternatively, the plastic component may be nearly inert. A composite made up of a bioactive material and an inert plastic may, if the composite possibly breaks, repair itself in the physiological environment under the mineralizing affect of the bioactive component.

Martin B. B. After Martin Street

7.7

15 Table 1

Hard Contraction The state of

1,3 ľ. 23 6

The suitable plasticization temperature (= setting temperature) of the plastic used is also determined according to the intended use of the composite. Plastics plasticizable within a temperature range of 5 °C...70 °C, preferably 5 37 °C...55 °C, are suited for most of the uses of the composite according to the present invention.

Especially suitable are plastics having a plasticization temperature in the vicinity of body temperature. The application of a product in plastic state will thus not 10 cause thermal damage in the tissue. Also, additives, such as proteins, possibly admixed with the composite would remain undamaged in connection with the preparation and application of the product. If the product implanted in a tissue is required to be soft, it is possible to select a 15 plastic component having a plasticization temperature somewhat lower than body temperature. Such a product can be applied on a hardened form, whereafter it will soften in the tissue.

There are, however, applications in which a very low (down 20

-10 °C) setting temperature of the plastic is preferable. One example is a situation in which it is desired to apply a piece or a component therein at a low temperature, whereafter the said piece or component is activated as the 25 temperature rises.

The plasticization temperature of the plastic component can be controlled very precisely, i.e. approx. ±1...±2 °C.

Relatively slowly setting plastics, that is plastics which are moldable for a certain period, i.e. approx.

15 s...30 min, preferably 1...10 min even after the 30 temperature of the plastic has been lowered to a temperature considerably lower than its setting temperature, are especially suitable. By the term "considerably lower" is meant here several degrees Celsius,

suitably approx. 10...15 °C. If the plastic is of a slowly setting type such as this, it is not very critical even if its setting temperature is relatively high, i.e. above 55 °C. The behavior described above is based on the slow mobility of large polymer molecules, in which case setting will occur for some time after the piece has cooled down.

Physiologically suitable types of plastic, plasticizable at a relatively low temperature, are previously known.

Poly(ortho esters) (J. Heller, (6, 7)) can be mentioned as an example.

Structure of the polymer:

An especially suitable plastic is a copolymer which is based on structural units such as a hydroxy acid; a hydroxy acid derivative such as a cyclic ester of a hydroxy acid, i.e. lactone; or a cyclic carbonate, such as trimethyl carbonate. L-, D- and DL-lactic acids; L-, D- and DL-lactides; and epsilon-caprolactone are highly suitable structural units.

A plastic component which is a copolymer based on L-lactide 20 and epsilon-caprolactone structural units is especially suitable for this use. The composition of the copolymer typically varies within the range

and the molar mass M of the copolymer is within the range 10,000...1,000,000 g/mol, suitably within the range 30,000...300,000 g/mol.

It is known that the polymerization of lactones and cyclic carbonates can be carried out by catalytic ring-opening polymerization. The catalyst used may be selected from many

known options, and is typically an organometallic compound, such as tin(II) octoate or triethylaluminum. The control of the molar mass in polymerization of this type is based on an optimal selection of the polymerization temperature and 5 period. It is also possible to use so-called initiator compounds, some typical examples of which are multivalent alcohols such as glycerol. In the polymerization, the polymer chains grow, starting from the -OH groups of the initiator compound, in which case the molar mass will be 10 the lower the larger the amount of initiator present. It is possible to affect the shape of the forming molecule by the structure of the multivalent alcohol. Thus, for example, glycerol forms a comb-like molecule and pentaerythritol a star-like molecule. Polymerization which opens the lactone 15 ring is described in, for example, literature reference (8).

The above-mentioned L-Lactide/epsilon-caprolactone copolymers based on hydroxy acid structural units are described in patent application No. FI 965067.

20 The control of the melting temperature of the plastic component, i.e. the polymer material, intended for the composite according to the invention is based on one hand on the selection of the monomer ratio in the initial substances and on the other hand on the control of the 25 molar mass in the copolymerization. Both of these factors together affect the melting temperature of the copolymer obtained, and thus only certain combinations produce the desired result. An example of such a composition is a copolymer which contains poly-L-lactide 20 % by weight and 30 E-caprolactone 80 % by weight. If the molar mass of this copolymer is approx. 30,000 g/mol, typically a melting temperature of approx. 40 °C is obtained. If, however, the molar mass of the said copolymer is approx. 300,000 g/mol, a melting temperature of approx. 48 °C is obtained. By the 35 control of the molar mass and the composition, a material with a melting temperature anywhere within the range

-10 °C...+100 °C is obtained.

In many applications, it is desired that the implant material degrades in a controlled manner, or reversely, has mechanical properties that remain stable for at least a certain period. The first stage in the biodegradability of the polymers of the present type is hydrolysis which cuts down the polymer chains until the molecule size is at a level at which the enzymatic functions of the body are capable of converting the degradation products into compounds natural for the body.

In terms of the degradation rate, the hydrophilicity of the polymer is crucial. Thus, in the copolymers being discussed it is possible to control their hydrolytic degradation rate by controlling the monomer composition, and thereby also hydrophilicity, and this, in accordance with what has been stated above, directly affects the degradation of the material in the body.

In terms of the invention, it is essential that, if the composition of the material is solely or almost solely 620 caprolactone, the balance being, for example, L-lactide,
DL-lactide, D-lactide or dimethyl carbonate, the polymer is almost stable in the body, or degrades very slowly, typically in the course of a number of years.

25 taneous control of the average molar mass of the copolymer by means of the preparation parameters, it is possible to exploit the previously known good biocompatibility of polyhydroxy acids. On the other hand, a waxy version of the copolymer material according to the invention can be rendered very rapidly degradable by controlling of the average molar mass and the monomer composition, as presented above. In this case the degradation period in the body is typically from a few days to a few weeks.

The degradation rate of a copolymer which contains poly-L-lactide and E-caprolactone can be controlled by means of the composition, so that when the lactide content is above 60 % by weight, the polymer degrades within a period of less than one month and when the lactide content is below 20 % by weight the degradation period is more than half a year. The degradation rate can be adjusted steplessly between these values by the control of the composition.

The compression resistance of a plastic component in solid 10 state is more than 10 Mpa and its tensile strength at break more than 10 Mpa. The material is plastic or rubbery.

Composite

The plastic component and/or the bioactive component of the composite according to the invention may also contain one or more additives. Examples which can be mentioned of such additives include the elements Ca, Na, P, B, Al, Zn, K, F, Si, Mg, Cl and Ti and their compounds such as oxides; drugs, proteins, proteoglycanes, sugars, growth factors, hormones, enzymes, collagen and antioxidants. It is, of course, the use of the composite that determines the selection of the additive or additives.

The composite according to the invention may form a dense or porous piece. The desired composite structure is obtained by the control of the ratio of the plastic

25 component to the bioactive component. The mixing ratio of the plastic component to the bioactive component can be controlled within quite wide limits, i.e. the concentration of the bioactive component may vary within a range of 1...98 % by weight of the composite. If the concentration of the bioactive component is very high, a composite structure is obtained in which the plastic component forms a binder between the particles of the bioactive component. In this case a rigid composite resembling a sugar lump is obtained. If the concentration of the bioactive component

is lower, i.e. less than 60 % by weight, a plastic-like composite is obtained which may be soft or resilient when so desired.

The composite may be, for example, a coating, membrane, net, thread, fiber, powder, or a piece such as a plate, a bead, a tube, a nail, a rod or an adhesive.

The composite according to the invention may also be prepared in connection with its use, immediately before it is being placed in a tissue (for example, a bone or a tooth). In this case the composite is prepared by "melting" the plastic component and the bioactive component together.

On the basis of the composite according to the invention, it is also possible to prepare a multi-layer composite, such as a multi-layer membrane, so that the plastic components of the different layers plasticize at different temperatures. A multi-layer composite may also be made up of different layers in which the biodegradability of the plastic components is different. The surface layer, or part of the surface layer (one side, one edge area) of an implant made from a multi-layer composite may thus be more rapidly or more slowly biodegradable than the deeper layers of the implant.

The composite according to the invention may also contain holes or channels. Optionally it is also possible to make so-called nutrition channels in the composite during an operation as the composite is being installed.

Applications:

The composite according to the invention can be used for preparing products suited for various uses, some examples being the following groups: bone or cartilage applications, tooth and jaw applications, cartilage coatings and soft tissue applications. Bone applications include, for

example, bone or cartilage filling material, a product intended for repairing long bones, a plate for repairing the back of the eye or facial bones, bone cement, an adhesive for joining the product to a tissue or tissues, an implant coating, a piece for repairing the vertebral column, and a skull plate. Examples of tooth and jaw applications include temporary tooth filling material, temporary or permanent tooth root filling material, a parodontal product, a product to be installed in the cavity remaining after the extraction of a tooth, tooth cement, 10 temporary tooth cement, temporary crown material, tooth implant coating, occlusion index rail, surgical paste and template material, which may be, for example, a paste, ring or thread which is placed in the gingival pocket. A tissue 15 guiding membrane or tube which is applicable to bone, tooth or soft tissue areas can also be mentioned. Further applications include protective cloth, wound dressing, adhesive tape, and a carrier for active agents and other biological structures (autogenic and allogenic bone) and 20 for drugs.

The suitable composite or composites are selected according to the use of the final product.

As to the bioactive component, it can be noted that a composite based on bioactive glass is especially well

25 suited for products which are hoped to promote mineralization (filling materials, tooth coatings, bone fillings, etc.) or which are hoped to form bone bonds for the reconstruction of bone deficiencies (bone fillings, bone cements, various implants, etc.). Composites based on a bioactive gel are especially well suited for final products the purpose of which is to release an active agent (for example, growth factor, hormone, cytostatic, etc.) for the treatment or prevention of a disease. A gel-based composite is also suitable for use in applications in which mineralization and the formation of bone bond are desirable. A gel-based composite is also suitable for the

reinforcement of products (the use of gel fibers for the reinforcement of plastic, bone pins, bone nails and bone screws, membranes, tendon tissue, filling materials, bone fillers, etc.).

The plastic materials may be plastic or rubbery, and their areas of use are divided so that the plastic-like materials will be used mostly for filling purposes and the rubber-like ones mostly for release purposes. Of course, again all types of blends are possible, and the selection of the plastic is mostly determined on the basis of the mechanical requirements.

Bone filler material to be used for the treatment of a fracture of an articular condyle can be taken as an example material. In the treatment of a condyle fracture, the

15 material is required to have sufficient mechanical strength in order for it to be able to support the cortical bone during the healing process. It must be moldable to fill a cavity in the porous bone. It must release inorganic and/or organic compounds promoting bone growth and mineralization for at least the duration of the healing process. Another example is the fracture of a long bone. In the treatment of the fracture, the material can be used for attaching (gluing) the bone ends in the fracture to each other. A third example is the attaching of small fractured fragments to the parent bone in, for example, a cartilage fracture.

Owing to the requirements presented above, the polymer matrix of a composite material must be plastic and melt to fluid state at approx. 42 °C. Its degradation time should in general be approx. 1 - 6 months, depending on the target 1 - 3 years. The other component of the material must be a sol-gel-produced Ca,P-containing xerogel or a bioactive glass in a granular or fibrous form, in an amount of approx. 60 - 70 % by weight of the material; this promotes the mineralization of the bone and the bonding of the bone to the material. A third component may be a sol-gel-

produced xerogel which contains bone growth factor, promoting bone regeneration in a bone cavity or other bone deficiency.

The following table (Table 1) shows the requirements set on a composite according to the invention as a function of the drug form:

Table 1

	injectable	implantable	needle-like rod-like
polymer matrix	rubbery	plastic or rubbery	plastic
melting temperature	polymer melts at 45° C viscosity low	melting temperature dependent on the drug	melting temperature dependent on the drug
gel	spray-dried beads	particle, fiber or monolith, depending on the shape of the piece	fiber

PREPARATION EXAMPLES

Example 1

10 Preparation of a matrix polymer

Chemicals used:

The copolymers were prepared from E-caprolactone monomer (E-CL), > 99 % pure, Fluka Chemika No. 21510, batch 335334/1 794, and D,L-lactide (D,L-LA), Purac, batch DF386H. The catalyst used was tin(II) octoate (Stannous 2-Ethylhexanoate; SnOct), 95 % pure, Sigma No. s-3252, batch 112H0248. The initiator used was glycerol, 99.5 % pure, Fluka BioChemika No. 49767, batch 42489/2 1094.

Purification and storage of the chemicals used:

There were molecular sieves (added on February 15, 1995) present in the E-caprolactone used, and the bottle was stored, protected from light, at +23 °C.

The D,L-lactide was purified by recrystallization from toluene (b.p. 110 °C) at a mass ratio of 1:2 toluene/lactide. The lactide dissolved in hot toluene was poured from a round-bottomed flask into a beaker. The lactide dissolved in toluene was allowed to recrystallize overnight at +23 °C. After filtration (medium-rapid filter paper) the crystallized lactide was dried under a lowered pressure for 4 d at +40 °C, the pressure being 4 mbar. The same steps were repeated. Thus, a twice recrystallized D,L-lactide, stored in an exsiccator in a refrigerator at +4 °C, was used in the polymerization runs.

15 The stannous octoate and glycerol were used as such. They were stored protected from light at +23 °C.

Preliminary preparations for the polymerization:

On the previous evening the lactide to be used for the polymerization was placed in a vacuum chamber at +40 °C 20 under a pressure of 4 mbar. The two-section reactor (volume approx. 0.7 l) required for the polymerization was assembled. In connection with the assembling of the reactor, the condition of the teflon seal of the reactor was checked. The proper closing of the upper and lower 25 sections of the reactor was ensured by using a closing device made from steel wire. Tap grease was applied lightly to the inside upper surfaces of the ground joints of the reactor.

Polymerization:

30 The oil bath used for the heating of the reactor was adjusted to 140 °C. The temperature of the oil varies during polymerization by 5 °C above and below the setting

16

value. First, approx. 10 g of the lactide was weighed into a small beaker (precision 0.0001 g). The stannous octoate and the glycerol were weighed and pipetted over the lactide by using a Pasteur pipette. Thereafter the beaker with its 5 contents was poured into the lower section of the reactor. The rest of the lactide was weighed by using another balance (precision 0.01 g). The E-caprolactone was either poured or pipetted over the lactide.

A magnetic stirrer was added to the reactor before the 10 closing of the reactor halves. The reactor was placed in a bath, and the stirring rate was set at 250 min⁻¹. The reactor was rinsed with argon (Aga, quality grade S, 99.99 %) for approx. 15 min. The argon was directed into the reactor via a glycerol lock. Finally the outer surface 15 of the reactor was lined with a foil. The stirring rate was reset at 125 min-1 when the forming copolymer began to become more viscous.

Copolymers prepared and their analysis:

Table 2 shows a summary of the E-caprolactone/D,L-lactide (E-CL/D,L-LA) copolymerization runs and the results of the 20 product analyses. In all of the polymerization runs the temperature was 140 °C and the polymerization time 24 h.

The molar mass values of the obtained copolymers, determined by gel permeation chromatography GPC, shown in 25 Table 2, are the number-average molar mass $M_{\rm n}$, the weightaverage molar mass $M_{\rm w}$, and polydispersity PD, obtained as the ratio ${\rm M}_{\rm w}/{\rm M}_{\rm n}$ of the above values. The same Table 2 shows the melting temperatures T_{m} , determined by differential scanning calorimetry (DSC), of the polymerization products obtained.

DE PORT DE MAN PROPERTIE

Table 2

Example	ε-CL/ D,L-LA- ratio	SnOct- conc. mol/mol	Glycerol conc. mol/mol	M _n 10 ⁻³ g/mol	M _w 10 ⁻³ g/mol	T _m °C
1	100/0	0,0001	0,005	45	60	56
2	80/20	0,0001	0,005	40	60	42
3	100/0	0,0001	0,25	4,3	5,2	35
4	60/40	0,0001	0,001	20	40	38

Properties of the polymer:

Table 2 shows typical product polymers and their properties.

5 GPC determinations:

In the determination of the molar mass values by means of GPC, the samples were prepared by dissolving 15 mg of the sample in 10 ml of chloroform. The columns used were columns of Polymer Laboratories Ltd, having a pore size of $10^2 - 10^5$ Å. The samples were analyzed by using an RI, i.e. refraction index, detector manufactured by Waters, the run time being 55 min at a flow rate of 1 ml/min. For the determination of the molar masses of the samples, an experimental calibration curve plotted by means of the polystyrene standards (PS) of Polymer Laboratories Ltd was used. Since experimental a-values and K-values of the Mark-Houwink equation are not available for the copolymers, the molar masses in Table 2 are not the absolute molar masses of the samples but relative values, compared with the PS standards.

DSC determinations:

In the DSC determinations, a sample of 5 - 10 g was heated at a rate of 10 °C/min in the calorimeter cell. In order to obtain the same thermal history for all of the samples, the samples were heated above their melting temperature, to a temperature above +80 °C, and were cooled to approx. - 50 °C. The T_m values, shown in Table 2, were registered from the curve of the second heating.

Example 2

Preparation of a composite material

An amount of 20 g of a polymer prepared according to Example 1 was taken. An amount of 20 g of a bioactive glass (type S53P4, reference 10) having an average particle size of 300 μm was taken. The components were poured into the Kneteter mixing head of a Brabender Co-Kneader apparatus, where the rotation speed was 50 rpm. The temperature of the Kneteter head had been set at 55 °C, and the mixing time was 15 min, whereafter the mixing head was opened and the homogenized material was recovered in a molten state.

The final product obtained was a homogeneous composite
20 material having a bioglass content of 50 % by weight. The
composite was stored in a gas-tight vessel under nitrogen
shield gas.

The above embodiments of the invention are only examples of the implementation of the idea according to the invention.

25 For a person skilled in the art it is clear that the various embodiments of the invention may vary within the claims presented below.

Literature references:

- 1. Heikkilä, J., Bioactive glass as a bone substitute in experimental and clinical bone defects, doctoral dissertation. University of Turku 1996.
- 5 2. Aho, A.J. & Heikkilä, J.T., Bone substitutes and related materials in chemical orthopaedics in <u>Advances in Tissue</u>

 <u>Banking</u> (Vol. 1), Phillips, Y.O., Versen, R., Strong, M.,

 Nather, A. (eds.), World Scientific 1997, pp. 73-107.
- 3. Hench, L.L., Bioactive glass and tissue regeneration, in Bioceramics, Kokubo et al. (eds.). Pergamon Press 1996, pp. 3-6.
 - 4. Ikada, Y., Bone-related polymeric biomaterials, in bioceramics, Kokubo et al. (eds.). Pergamon Press 1996, pp. 15 18.
- 15 5. Bonfield, W., Composite Biomaterials, in <u>Bioceramics</u>, Kokubo <u>et al.</u>, (eds.). Pergamon Press 1996, pp. 11 13.
 - 6. Heller, J., Development of poly(ortho esters): a historical overview, <u>Biomaterials</u>, <u>11</u> (1990), 659-665.
- 7. Heller, J., Roshos, K.V., Duncan, R., Use of poly(ortho 20 esters) in the controlled release of therapeutic agents, Macroimol. Chem., Macromol. Symp. 70/71 (1993), 163-171.
 - 8. I Ylikangas, "The polymerization of epsilon-caprolactone with stannous catalysts", Polymer Technology Publications, Series No. 15, Helsinki University of Technology 1993, 1 23.
 - 9. C Jeffrey Brinker & George W Scherer "Sol-Gel Science The Physics and Chemistry of Sol-Gel Processing". Academic Press, Inc., San Diego, CA 92101, 1990.

The first first three trees that the first first the first f

10. Ö H Andersson & K H Karlsson "Corrosion of bioactive glass under various in vitro conditions". Advances in Biomaterials No. 8, Elsevier (Amsterdam) 1990.

11. C.P.A.T. Klein et al., Biomaterials (1995) 16:715-719.

er mesenskerson († 1877-1974) in vir istrick de frank in 1870-1985 besker beskrive blikker in de frank in de f

CLAIMS

- 1. A composite intended for medical use, in particular surgical or therapeutic use, characterized in that it comprises
- a thermoplastic component plasticizable within the temperature range -10 °C...+100 °C, which is substantially made up of hydroxy acids and structural units derived from hydroxy acid derivatives, and the molar mass of which is within the range 10,000 - 1,000,000 g/mol, and which degrades in the body typically within a period ranging from 10 a few days to several years, and which in its solid state is a mechanically strong plastic or rubbery material, and - a bioactive component, which is a bioactive glass, a bioactive xerogel, a bioactive ceramic material, coral or a coral-based product, or a bioactive glass ceramic material.
- 15 2. The composite according to Claim 1, characterized in that the plastic component is plasticizable within the temperature range 5 °C...70 °C, preferably within the temperature range 37 °C...55 °C.
- 3. The composite according to Claim 1 or 2, characterized in that the plasticized plastic component remains moldable for a certain period even after the temperature of the composite has been lowered to a temperature which is considerably lower than the setting temperature of the said plastic component.
- 25 4. The composite according to Claim 1, 2 or 3, characterized in that the plastic component is biodegradable in a controlled manner within the time range 1 week - 3 years.
- 5. The composite according to Claim 4, characterized in 30 that the structural unit is an L-, D- or DL-lactic acid; an L-, D- or DL-lactide; or epsilon-caprolactone.

- 6. The composite according to Claim 5, characterized in that the plastic component is a copolymer based on structural units of L-lactide and epsilon-caprolactone.
- 7. The composite according to Claim 6, characterized in that the composition of the copolymer is within the range

8. The composite according to Claim 7, characterized in 10 that

- 9. The composite according to Claim 8, characterized in that the molar mass of the copolymer is approx. 30,000 = 300,000 g/mol.
 - 10. The composite according to any of the above claims, characterized in that the bioactive component is present as separate particles in the composite.
- 20 11. The composite according to Claim 10, characterized in that the separate particles are fibers, porous pieces, microparticles or glass beads.
- 12. The composite according to any of the above claims, characterized in that the plastic component and/or the bioactive component contains one or more additives.
 - 13. The composite according to any of the above claims, characterized in that the plastic component and the bioactive component form a dense piece.
 - 14. The composite according to any of Claims 1 12,

characterized in that the plastic component forms a porous piece.

- 15. A blend intended for the preparation of a composite according to any of Claims 1 14, characterized in that the plastic component and the bioactive component in the blend are in powder form.
- 16. A coating, membrane, net, powder, fiber, thread,
 adhesive, or a piece such as a plate, bead, tube, nail or
 rod, prepared from the composite according to any of Claims
 10 1 14.
- 17. The use of a composite according to any of Claims 1 14 for the preparation of any of the following products:
 a bone or cartilage application, such as a filling material for bone or cartilage, a product intended for the 15 repairing of long bones, a plate for the repairing of the back of the eye or facial bones, a bone cement, an adhesive for joining the product to a tissue or tissues, an implant coating, a piece for the repairing of the vertebral column, and a skull plate,
- 20 a tooth or jaw application, such as a temporary tooth filling material, a temporary or permanent tooth root filling material, a parodontal product, a product to be placed in the cavity left by an extracted tooth, a tooth cement, a temporary tooth cement, a temporary crown
- 25 material, a tooth implant coating, an occlusion index rail, a surgical paste, and a template material, which may be, for example, a paste, ring or thread to be fitted in a gingival pocket,
 - a cartilage coating,
- 30 a tissue guiding membrane or tube,
 - a protective cloth, a wound dressing, or an adhesive tape,
 - a carrier for an active agent, such as a drug, or for some other biological structure.

Docket No. TUR-087

Declaration For U.S. Patent Application

As a below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural

names are listed below) TITLE) NOVEL PLA	of the subject t ASTIC BASED	matter which is claimed COMPOSITE AND	ed and for which a patent is s ITS USE	sought on the invention entitled (INSERT		
the specification of whi	ch					
(Check one of 1, 2, or 3.)						
	and was	amended on 23 Dec	cember 1999	<u></u>		
	3 was filed U.S. Appand was	d on plication Serial No amended on	as (if applicable)			
I hereby state that I have amended by any amended	e reviewed an	d understand the com		I specification, including the claim(s), as		
I acknowledge the duty t §1.56.	o disclose infor	mation which is mate	rial to patentability as define	d in Title 37, Code of Federal Regulations,		
I hereby claim foreign p certificate listed below a before that of the applic	na nave aiso id	entified below any for	d States Code, §119 of any freign application for patent o	oreign application for patent or inventor's r inventor's certificate having a filing date		
(List prior foreign applications.)	972890 (Number)	Finland (Country)	8/7/97 (Day/Month/Year Filed)	Priority Claimed		
	(Number) See	(Country) attached list for addit	(Day/Month/Year Filed) ional prior foreign application	· —		
provided by the first par	on of the claim agraph of Title e of Federal Re	s of this application: 35, United States Coegulations, §1.56, wh	is not disclosed in the prior de. §112. I acknowledge the	s application listed below and, insofar as United States application in the manner duty to disclose material information as ling date of the prior application and the		
	(Application	n Serial No.) (F	iling Date) (Status)	-		
I hereby appoint as princ	cipal attorney J	ames C. Lydon, Reg.	No. 30,082 and Kevin C. B	rown, Reg. No. 32,402.		
Please direct all commu	nications to the	following address:	James C. Lydon Lydon & Brown, LLP 100 Daingerfield Road, St Alexandria, Virginia 2231 Telephone: (703) 838-044 Facsimile: (703) 838-044	4 5		
pelief are believed to be t like so made are punisha	rue; and furthe ble by fine or i	r that these statement imprisonment, or both	s were made with the knowle	all statements made on information and edge that willful false statements and the le 18 of the United States Code and that issued thereon.		
Full name of first or sole	inventor: A	llan AHO				
nventor's Signature:			Date:			
Residence: <u>Yliopiston</u>	<u>katu 1 A 9, FII</u>	N-20100 Turku, Finla	nd			
Post Office Address: sa						

Full name of second inventor: Jukka SEPPÄLÄ	
, , , , , , , , , , , , , , , , , , ,	Date: 09-Feb - 2000
Residence: Mäkipellontje 18 C, FIN-00320 Helsinki, Finland	Date. 12 100 XXXX
Citizenship: Finnish	OIA
Post Office Address: same as residence	FFD
Same as residence	3 2000 C
Full name of third inventor: _Antti YLI-URPO	
	SUPPLEASE IN THE
Inventor's Signature: Residence: Värttinäkatu 17, FIN-20660 Littoinen, Finland	Date:
Citizenship: Finnish	
Post Office Address: same as residence	
Full name of fourth investors I. : IVEVIVVV "	
Full name of fourth inventor:	
Inventor's Signature:	Date:
Residence: Vitanovantie 39, FIN-20900 Turku, Finland	
Citizenship: Finnish	
Post Office Address: same as residence	
Full name of fifth inventor: <u>Ilkka KANGASNIEMI</u>	
Inventor's Signature:	
Residence: Köydenpunojankatu 2 B 5, FIN-20300 Turku, Finland	
Citizenship: Finnish	
Post Office Address: <u>same as residence</u>	
diamental series	
Full name of sixth inventor:	
is Inventor's Signature:	Date:
Residence:	
Citizenship:	
Post Office Address:	
Full name of seventh inventor:	
Inventor's Signature:	Date:
Residence:	
Citizenship:	
Post Office Address:	
Full name of eighth inventor:	
Inventor's Signature:	
Residence:	
Citizenship:	
Post Office Address:	

Declaration For U.S. Patent Application



As a below named inventor, I hereby declare that:

Mrs manidamaa	nost office addre	ss and citizenship	are as stated	helow next to	n my name
Miv residence.	post office addre	ss and chizenship	are as stated	Delow Heat u	my name.

(if plural names are lentitled (INSERT T	listed below) of the subj	ject matter which is	claimed and for which a patent is	sought on the invention
Novel pl	astic based co	mposite and	its use	,
the specification of w				,
(Check one of	1 is attached h	ereto.		
1, 2, or 3.)	2. X was filed on	6 July 1998	3 as	
	International	PCT Application Ser	as rial No. PCT/FI98/00572	
	and was ame	nded on 23 Dece	ember 1999	
			(if applicable)	
	was filed on		as	
	U.S. Applica	tion Serial No		
	and was ame	nded on	(if amplicable)	
			(if applicable) f the characidantified appointmention	including the claim(s)
as amended by any a	have reviewed and under amendment referred to a	bove.	f the above-identified specification	i, including the claim(3),
.Code of Federal Reg	gulations, §1.56.		o the examination of this application	
inventor's certificate	gn priority benefits und listed below and have a before that of the applic	also identified below	States Code, §119 of any foreign any foreign application for patent ity is claimed:	or inventor's certificate
maving a minig date	nerore mar or me appric			Priority Claimed
(List prior	972890	Finland		X Yes No
foreign applications.)	(Number)	(Country)		Yes No
	(Number)		(Day/Month/Year Filed) nal prior foreign applications	
information as defin	the first paragraph of 7 ed in Title 37, Code of national or PCT internat	Federal Regulations,	ss Code, §112, I acknowledge the §1.56, which occurred between this application:	ne filing date of the prior
		ial No.) (Fil		
I hereby appoint as	principal attorneys Jame	es C. Lydon, Reg. N	o. 30,082 and Kevin C. Brown, F	Reg. No. 32,402.
	nmunications to the follo	owing address: Jan Ly 10d -Su Al Te		
and belief are believ	ed to be true; and furthe le are punishable by find willful false statements	r that these statement e or imprisonment, o	wledge are true and that all statems were made with the knowledge the both, under Section 1001 of Tit ralidity of the application or any p	le 18 of the United States
Full name of first o	· ·	, Allan		2111200
Inventor's Signature	e:Mlan	mo		Date: 24,1,200
	Liopistonkatu	1 A 9, FIN-2	0100 Turku, Finland	
Citizenship:	rinnish			
Post Office Address	s: same as re	sidence		

	/ O / A	
J	FFR 2	
	2 0) FEB 2 3 2000 (2)	
	Full name of second inventor SEPPALA, Jukka	4 40 11 1000
	Inventor's Signature: full fine	Date: 19.11.1999
	Residence: Mäkipellontie 18 C, FIN-00320 Helsinki, Finlan	d/
	Citizenship: Finnish	
	Post Office Address: same as residence	
'n	3~ OD	
	Full name of third inventor: YLI-URPO, Antti	<u> </u>
	Inventor's Signature:	Date: 21, 7, 2000
	Residence: Värttinäkatu 17, FIN-20660 Littoinen, Finland	
	Citizenship: Finnish	
	Post Office Address: same as residence	
	A4-00	
	Full name of fourth inventor: HEIKKILÄ Jouni	011600
ane is.	Inventor's Signature:	Date: 21.1.2000
15.00 15.00	Residence: Vitanovantie 39, FIN-20900 Turku, Finland	
W H H H H	Citizenship: Finnish	
	•Post Office Address:same as residence	
House House	5-00	
man dang	Full name of fifth inventor:KANGASNIEMI, Ilkka	0110
l,I	Inventor's Signature:	_ Date: 91.1.2000
Aug Bus	Residence: Köydenpunojankatu 2 B 5, FIN-20300 Turku, Finla	and FLX
State State	Citizenship: Finnish	
And dead	Post Office Address: same as residence	
gra. Era		
22.00	Full name of sixth inventor:	
	Inventor's Signature:	Date:
	Residence:	
	Citizenship:	
	Post Office Address: same as residence	
	Full name of seventh inventor:	
	Inventor's Signature:	
	Residence:	
	Citizenship:	
	Post Office Address: same as residence	
	Full name of eighth inventor:	
	Inventor's Signature:	Date:
	Residence:	
	Citizenship:	
	Post Office Address: same as residence	